

Digital Clamp Meter

- CM240



+ Performance Specifications

	Range	Accuracy
AC Voltage	2V / 20V / 200V	$\pm (1.2\%+5d)$
	600V	$\pm (1.5\%+5d)$
DC Voltage	200mV	$\pm (0.8\%+5d)$
	2V / 20V / 200V	$\pm (0.8\%+5d)$
	600V	$\pm (1.0\%+5d)$
AC Current	2.000A	$\pm (4\%+20d) \leq 0.4A, \pm (3\%+15d)$
	20.00A	$\pm (3\%+15d) \leq 0.4A, \pm (2\%+10d)$
	200.0A / 400A	$\pm (2\%+5d)$
Resistance	200.0 Ω	$\pm (1.2\%+5d)$
	2.000k Ω / 20.00k Ω / 200.0k Ω	$\pm (1\%+3d)$
	2.000M Ω	$\pm (1.2\%+5d)$
	20.00M Ω	$\pm (1.5\%+5d)$

Features

Display Count	2000
Auto Range	√
Data Hold	√
Jaw Capacity	28mm
Diode	√
Continuity Buzzer	√
MAX Mode	√
LBD	Low Battery indication
Auto Power-off	√

General

Power	2 x 1.5V AAA batteries
Dimension (W×H×D)	65 x 177 x 28 (mm)
Weight (without package)	186 g
Safety Rating	CE, CAT III, 600V

