



## PORTABLE TYPE

### FEATURES :

- Calculate Dew point temperature and Wet bulb temperature in seconds
- HOLD function: Freeze current readings on LCD ,
- Maximum/Minimum/Average : Record since powered on , recall to check
- Auto power off : Save power energy when not used
- Water resistant unit IPX4 rating
- Option: Wider temperature range
- Temperature unit: Switchable
- Battery low indicator
- USB icon display stands for recording in process (98575)
- LCD size: 40x33mm dual display Temperature and RH%
- Optional backlight function for working in dark area
- Tripod mountable receptacle for long time logging purposes.

All Thermo-hygro meters  
calculate DEW POINT Temp.  
& WET BULB Temp.  
in seconds

### Supplied with :

Meter x1, Batteries x3, Manual x 1, Plain box x1 , CD x1 (Software)(98875.98575)  
USB cable x1 (98875.98575)

	98871	98873	98875	98575	98874D	98877
Temp.range	-20.0~50.0°C (-4.0~122.0°F)					
Accuracy	±0.6C (-10~50°C) , others ±1°C					
External Temp. probe&range	N/A				YES (-20~70°C (-4~158°F)	
Ext.emp.accuracy	N/A				±0.6°C (1.2°F)	
RH % range & accuracy	0.0~100.0% ; ±3%(10-90%),others +5%					
Dew Point & Wet bulb	YES					
Wet Bulb Global Temp.(WBGT)&Heat Index	N/A	N/A	YES		N/A	YES
Memory	N/A	99 point	Real time 64K	Off line 32K	Off line 32K	Off line 32K
Meter size	160*55*29mm (Meter) , Sensor tip( 31mm)					
SD card storage(8G)	98871_SD	98873_SD	98875_SD	98575_SD	98874_SD	98877_SD