

WATER QUALITY TESTER (COMBO PEN)



(99720)

Supplied with :

Meter x1, Batteries x2, manual x1, carrying pouch x1, Hard carrying case x1, wrist strip, soaking solution, pH solution, Conductivity solution x1, Conductivity electrode, pH electrode (built-on)

Optional electrode: ORP electrode

FEATURES: 99702 Four (4) in one Con/TDS/Salt/Temp. combo pen

- A combo smart pen, buy one get 4 parameters with less cost
- Powered by AAA x 4 pcs batteries
- Dual display Conductivity or TDS or Salt and temperature readings

Self-calibrate with supplied conductivity solution

Supplied with Meter x1, Cond. solution x1, Soak solution x1, batteries x4, manual and wrist strip, hard case.



Model No.	99702 (4 in one)		
Type	Cond.	TDS	Salt
Range	0~2000µS, 2.00~20.00mS	0~1300ppm 1.30~13.00ppt	0~1000ppm, 1.00~12.00ppt
Accuracy	±2%FS (Cond. TDS Salt)		
Resolution	1µS/ 0.01mS	1ppm/ 0.01ppt	1ppm/ 0.01ppt
ATC	0~50°C		
Calibration	Cond: 0µS/ 1413µS/ 12.88mS		

FEATURES :

- A very smart pen type combo water quality tester, buy one get more than 6 parameter measurement, microprocessor based for fast and accurate display
- A new shape design powered by AAA DC1.5V x 4 pcs batteries
- Simple to calibrate by one button, may float on water
- Compact housing Ip57 water resistant design
- Large LCD display pH or ORP or Cond. or TDS or Salt and temperature simultaneously
- ATC stands for Automatic Temperature Compensation
- MSC stands for Manually salinity calibration
- MAC stands for Manually altitude compensation
- Data hold freezes current reading, Maximum/Minimum function
- Temp.C and F are selectable, battery low indication. Auto power off in 10 minutes
- Easy to replace with new electrode to maintain meter life
- Replacement electrode modules are easy to replace and the type of electrode would be recognized automatically and shown in display during insertion
- Wide range pH measurement from -2 to 16

Model No.	99720 (6 in one)		
Type	pH	ORP	Temp.
Range	-2~16.00	-1000~1000	0~90°C
Accuracy	±0.01+1dg	±2+1dg	±0.2°C+1dg
Resolution	0.01pH	1mV	0.1°C
ATC	0~90°C		
Calibration	pH: 4.00/ 7.00/ 10.01		
Type	Cond.	TDS	Salt
Range	0~2000µS, 2.00~20.00mS	0~1300ppm 1.30~13.00ppt	0~1000ppm, 1.00~12.00ppt
Accuracy	±2%FS (Cond. TDS Salt)		
Resolution	1µS/ 0.01mS	1ppm/ 0.01ppt	1ppm/ 0.01ppt
ATC	0~50°C		
Calibration	Cond: 0µS/ 1413µS/ 12.88mS		
Power	AAA batteries x 4 pcs		
Weight	Meter : 135 g (battery included), Kit: 780g		
Dimension	Meter : 195 X40x36mm (Kit: 230x205x50mm)		